



## INSTALLATION INSTRUCTIONS

### P/N 65226 – CLEAR FLOAT LEVEL SIGHT SCREW FOR HOLLEY CARBURETORS

1. Install O-ring on screw as shown.



2. Remove float bowl level screw from Holley carb and adjust float level per Holley instructions.
3. Lubricate the O-ring and threads with a silicone lubricant and install Clear-View Sight Plug until snug using your fingers only. The O-ring will lock and seal the plug.
4. Look through the Sight Plug to note fuel level.
5. Due to the new blend of fuels including E-85, we recommend using the Clear Sight Screw to set fuel level only. After setting float bowl level, replace Clear Sight Screws with original brass plugs.
6. Clear Float Level Sight Screws are not compatible with any Ethanol or Methanol fuels.
7. Over time, the plastic Sight Plug may begin to haze over due to fuel, heat and sun exposure. To remove this haze simply polish the plug using 600 grit or finer sandpaper.

**For Technical Assistance, Call Moroso's Tech Line at  
(203) 458-0542, 458-0546 8:30am – 5:00pm Eastern Time**

MOROSO PERFORMANCE PRODUCTS, INC  
80 CARTER DR • GUILFORD, CT 06437  
Phone: (203) 453-6571 • Fax: (203) 453-6906