



Transmission Mount/Solid Crossmember Mustang 2005-UP Part# C3603

Parts List

- (1) Transmission Mount Assembly (4) spacers
(1) M10-1.5 x 50mm Grade 8 Bolt

Installation instructions

1. Place the transmission in neutral and hoist the vehicle into position.
While the vehicle is in the air, using a suitable transmission jack, support the transmission.
2. Remove the 1 crossmember to transmission bolt
3. Remove the 4 outer-most 12 mm crossmember bolts (retain for re-use).
4. Remove the stock mount.
5. Install the new C3603 crossmember re-using the 4 retained 12 mm bolts **NOTE: There are 4 spacers provided in the kit. They are to be positioned between the heads of the (4) 12 mm bolts and bottom of the new mount's surface. These spacers will retain the proper mounting position for the optional Moroso drive shaft loop (P/N C3160) and/or exhaust hanger provision for some aftermarket exhausts.**
7. With spacers properly positioned torque the (4) 12 mm to 46lb-ft (Ford Motor Company workshop Manual).
8. Fasten the transmission to the new mount using the provided m10x1.5x50mm bolt torque to 52lb-ft (Ford Motor Company Workshop Manual).
9. Lower the vehicle and road test

*For Technical Assistance, call Competition Engineering's Tech Line at
(203) 458-0542, (203) 458 0546 8:30am-5:00pm Eastern Time*

COMPETITION ENGINEERING
80 Carter Drive • Guilford, CT 06437

Rev.A
050609

C3603INST

Phone: (203) 453-5200 • Fax: (203) 453-6906

Visit Us At www.competitionengineering.com